

MBS-1018-1 , 10" X 18" HORIZONTAL DUAL MITERING BANDSAW

413411

JET Dual Mitering Horizontal bandsaws unique design head dual miters both left and right for quick angle cuts.



FEATURES

- Heavy duty construction reduces vibration and deflection
- Built in, self propelled blade brush prevents chip build up in blade guides
- Blade tension gauge helps to ensure the blade is in the correct cutting position
- Magnetic starter for low voltage and lost phase protection
- Automatic blade breakage sensor detects accidental breakage and interrupts the power
- Power switch with safety key prevents accidental start up
- CSA/CUS: Following strict guidelines and electrical requirements, this JET saw is CSA/CUS certified
- Blade is fully guarded for Operator safety
- Automatic shut off switch stops the sawing process
- Hydraulic downfeed control is easily adjusted enabling feed rates to evolve with variable types of materials
- Intergrated ressurized wash hose for easy machine clean up
- Quick action vise on 10" saws
- STANDARD EQUIPEMENT
- Quick action vise on 10" saws
- Blade Tension Gauge
- Coolant System
- Adjustable material stop
- Intergrated ressurized wash hose for easy machine clean up



JET RED ASSURANCE 2-YEAR WARRANTY

JET warrants every product it sells. If one of our tools needs service or repair, one of our Authorized Service Centers located throughout the United States can give you quick service. In most cases, any of these JPW Industries Authorized Service Centers can authorize warranty repair, assist you in obtaining parts, or perform routine maintenance and major repair on your JET tools. For the name of an Authorized Service Center in your area call 1-800-274-6848.

STAND BEHIND YOUR WORK™



550+ SERVICE CENTERS NATIONWIDE

INDUSTRY-LEADING WARRANTIES

EXPERT TECHNICAL SERVICE

MBS-1018-1 , 10" X 18" HORIZONTAL DUAL MITERING BANDSAW

413411

SPECIFICATIONS

Cutting Capacity (W x D) (In.)	10" x 18"
Round at 90 Degrees (In.)	10
Round at 45 Degrees (In.)	10
Rectangle at 90 Degrees (In.)	10" x 17"
Rectangle at 45 Degrees (In.)	10 x 12
Head Movement (Deg.)	'45R ,60L
Blade Size (In.)	1 x 0.032 x 144
Blade Wheel Diameter (In.)	14-1/4
Blade Speed (SFPM)	50, 125, 200, 275
Bed Height (In.)	'22-1/2
Motor (HP)	2 HP 230V, 1 Phase
Overall Dimensions (L x W x H) (In.)	79 x 36 x 46
Weight (Lbs.)	1144



STAND BEHIND YOUR WORK™



550+ SERVICE CENTERS NATIONWIDE

INDUSTRY-LEADING WARRANTIES

EXPERT TECHNICAL SERVICE